



TECHNICAL DATA

Rated input current	2 A
Rated frequency	50 Hz
Rated voltage	230 V
Rated output power	240 W
Standby power	0.3 W
Duty cycle	2 Min. ON (120W) / 12 Min. OFF or 0.5 Min. (240 W), 0.5 Min (120W) / 9 Min. OFF
Service life	10 000 cycles
Dimensions (l x w x h)	182 mm x 84.5 mm x 36.5 mm / 8.590" x 3.328" x 1.437"
Weight	317 g
Ambient conditions during operation	+5 °C to +40 °C at 10 % to 85 % relative air humidity (non-condensing), 27 °C max. dew point, up to an altitude of 2000 m
Ambient conditions during transport and storage	-25 °C to +70 °C at 5 % to 90 % relative humidity (non-condensing) +38 °C max. dew point temperatures of +55 °C to +70 °C only for periods not exceeding 24h
Compatibility	all LOGICDATA-handsets except LOGICtouch family all LOGICDATA-actuators except LOGICdrive family LOGIClink communication hub
Degree of protection (IEC 60529)	IP 20
Applicable standards	RoHS 2011/65/EU REACH regulation (EG) Nr. 1907/2006 EMV 2014/30/EU LVD directive 2014/35/EG Eco-Design directive 2009/125/EG Machinery directive 2006/42/EC
Interference immunity to ESD in accordance with EN 61000-6-2	Contact discharge 4kV Air discharge 8kV
Order code	SMARTneo-2-x-y-EU