



SMARTneo

Smaller. Smarter. Optimized.

DESCRIPTION

The SMARTneo is a size- and function-optimized control unit and provides more freedom of design to height-adjustable tables. The control unit is available in two versions: SMARTneo and SMARTneo-pro. With special features available like Bluetooth connectivity, direct input for collision detection with an external sensor as well as the possibility to operate via LOGIC-cell, SMARTneo-pro is the next evolution following a long and successful history of LOGICDATA's switched mode power supply control boxes.



FEATURES


- Compact & low-profile design
- Freely programmable
 - height limits
 - speed & load control
 - reset & stop conditions
 - collision detection
 - many more...
- Highly efficient switched mode power supply (SMPS)
- Cascading of 2 control boxes
- Compatible with all LOGICDATA hand controls
- Compatible with LOGIClink

Contact Headquarters

LOGICDATA Electronic & Software Entwicklungs GmbH
Wirtschaftspark 18, 8530 Deutschlandsberg, office.at@logicdata.net

North America

LOGICDATA North America Inc., 5300 Broadmoor Ave SE,
Suite D, Grand Rapids, MI 49512, USA, office.na@logicdata.net



TECHNICAL DATA

Rated input current	4 A
Rated frequency	60 Hz
Rated voltage	120 V
Rated output power	240 W
Standby power	0.3 W
Duty cycle	2 Min. ON (120W) / 18 Min. OFF or 0.5 Min. (240 W), 0.5 Min (120W) / 9 Min. OFF
Dimensions (l x w x h)	218.2 × 84.5 × 36.5 mm / 8.590 " × 3.328 " × 1.437 "
Weight	338 g
Ambient conditions during operation	+5 °C to +40 °C at max. 68% relative air humidity (non-condensing), up to an altitude of 2 000 m.
Ambient conditions during transport and storage	-25 °C to +40 °C at max. 68% relative air humidity (non-condensing). +40 °C to +60 °C at max. 32% relative air humidity (non-condensing). Temperatures of more than +40 °C for periods not exceeding 10h. Product must be acclimatised to acceptable operating conditions before assembly. Contact LOGICDATA for exact specifications.
Compatibility	Visit LOGICDATA.net for a full list of compatible products.
Degree of protection (IEC 60529)	IP 20
Applicable standards	UL 60950-1 2nd Edition: 2014-10-14 CAN/CSA C22.2 No. 60950-1-07, 2nd Edition, 2014-10 FCC Title 47 subpart 15 unintended radiator
Interference immunity to ESD in accordance with EN 61000-6-2	Contact discharge 4kV Air discharge 8kV
Order code	SMARTneo-2-x-y-US